

Next generation of light hardwood H2s LVL

SmartLVL[®] 16



- Innovation powered new LVL stiffness and strength grade for Australia
- SmartLVL 16 is a similar weight of a Pinus pinaster based softwood LVL
- Light Hardwood veneers give superior nail plate tooth capacity compared to most softwood LVL's. (Nail plate capacity is proprietary data unique to the respective nail plate supplier)
- JD3 joint strength for nails, screws and bolts.
- Supplied as H2s glue line treated with H2 glue line/face veneer treatment available on request. Preservative is therefore evenly distributed through full cross section, unlike envelope treatments
- Further post production preservative treatable to H3

SmartLVL 16

Availability:

Packs ONLY

LVL 16 Size	Stock lengths (m)									
	3.6	4.2	4.8	5.4	6.0	6.6	7.2	9.6	10.8	12.0
90 x 35	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
120 x 35	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
140 x 35	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
190 x 35	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

SmartLVL 16 may be purchased by negotiation as a special order, at a length different to that shown above. For details, contact your SmartFrame Sales Representative in your respective state.

Characteristic strength properties:

A full suite of Engineering properties for SmartLVL 16 is available by contacting the Technical Support Helpline on 1300 668 260 or by email at techsupport@tilling.com.au.

Available from:

Tilling Timber Pty Ltd

Head Office

Victoria

31-45 Orchard Street,
Kilsyth Vic 3137

email: sales@tilling.com.au

Phone +61 3 9725 0222

Fax +61 3 9725 3045

New South Wales

109 Kurrajong Avenue,
Mt Druitt, NSW 2770

email: nswsales@tilling.com.au

Phone +61 2 9677 2600

Fax +61 2 9677 2500

Queensland

84 Magnesium Drive,
Crestmead QLD 4132

email: qldsales@tilling.com.au

Phone +61 7 3440 5400

Fax +61 7 3440 5444

Western Australia

10 Cartwright Drive
Forrestdale WA 6112

email: wasaes@tilling.com.au

Phone +61 8 9399 1609

Fax +61 8 9399 1065

South Australia

5-9 Woomera Ave
Edinburgh SA 5111

email: sasales@tilling.com.au

Phone +61 8 8345 1966

Fax +61 8 8345 1977

The information contained in this product brochure is current as at November 2018 and is based on data available to Tilling Timber Pty Ltd at the time of going to print. Tilling Timber Pty Ltd has used its reasonable endeavours to ensure the accuracy and reliability of the information contained in this document and, to the extent permitted by law, will not be liable for any inaccuracies, omissions or errors in this information nor for any actions taken in reliance on this information. Tilling Timber Pty Ltd reserves the right to change the information contained in this document without prior notice. It is important that you call the Tech Support customer Helpline on 1300 668 690 to confirm that you have the most up to date information available.

